





CR135110



CR135110

Input Voltage AC220-240V, Multivoltage
Light Power 18W
Luminous flux ~2960lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



CR267110



CR267110

Input Voltage AC220-240V, Multivoltage
Light Power 2*18W
Luminous flux ~2970lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option

CR387110





CR387110

Input Voltage AC220-240V, Multivoltage
Light Power 3*18W
Luminous flux ~4420lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option

CR128110

CR128110 TRIM-LESS



Input Voltage AC220-240V, Multivoltage
Light Power 18W
Luminous flux ~1320lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



CR260110

CR260110 TRIM-LESS


Input Voltage AC220-240V, Multivoltage
Light Power 2*18W
Luminous flux ~2965lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



CR380110

CR380110 TRIM-LESS

Input Voltage AC220-240V, Multivoltage
Light Power 3*18W
Luminous flux ~4425lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 25°, 40°, 60°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



RETAIL 20 SERIES

lighting product designers and mold management

